

LN SATA SERIES

STANDALONE DVR



■ Model

DH-DVR0404/0804/1604LN-S	4/8/16 channel audio/video basic model
DH-DVR0404/0804/1604LNL-S	4/8/16 channel loop and matrix combination model
DH-DVR0404/0804/1604LNH-S	4/8/16 channel loop matrix and audio/video model

■ Features

- Most competitive price and high cost effectiveness
- H.264 compression algorithm ideal for standalone DVR
- Realtime live display up to 16 cameras, 100/120 fps recording for CIF
- Pentaplex function: live, recording, playback, backup & remote access
- 8 HDDs supported & CD-RW/DVD-RW supported
- Multiple control methods: IR remote controller, DAHUA keyboard, USB mouse and network keyboard.
- Smart video detection: motion detection, camera blank, video loss.
- Smart camera settings: privacy masking, camera lock, color setting, and title display
- Pan Tilt Zoom and Speed Dome Control: more than 60 protocols supported, preset, scan, auto pan, auto tour, pattern, auxiliary function supported. And with Dahua Speed Dome, 3D intelligent positioning function supported.
- 16 channel audio inputs and cross talk supported
- Easy backup methods: USB devices, CD-RW/DVD-RW & network download
- Alarm triggering screen tips, buzzer, PTZ preset, e-mail, FTP upload.
- Smart HDDs Management: non-working HDD hibernation, HDD faulty alarm, Raid function.
- Powerful network software: built-in web server, multi-DVR client & CMS. Networking access for remote live viewing, recording, playback, setting, system status, event log, e-mail & ftp function.

System	
Main Processor	High performance embedded microprocessor
Operating System	Embedded LINUX
System Resources	Pentaplex function: live, recording, playback, backup & remote access
User Interface	GUI, on-screen menu tips.
Control Device	Front panel, USB mouse, DAHUA keyboard, IR remote control, network keyboard.
Input Method	Numerical/Character/Denotation
System Status	HDD status, data stream statistics, Log record, bios version, on-line user etc.

Video							
Video Input	4/8/16 channel, BNC, 1.0Vp-p, 75 , looping (optional)						
Video Output	2 channel TV output BNC, 1.0Vp-p, 75 , 1 VGA output						
Video Standards	PAL (625Line 50f/s) NTSC (525Line 60f/s)						
Video Compression	H.264						
Video Resolution	<table border="1"> <thead> <tr> <th>FORMAT</th> <th>NTSC</th> <th>PAL</th> </tr> </thead> <tbody> <tr> <td>CIF</td> <td>352 X 240</td> <td>352 X 288</td> </tr> </tbody> </table>	FORMAT	NTSC	PAL	CIF	352 X 240	352 X 288
FORMAT	NTSC	PAL					
CIF	352 X 240	352 X 288					
Video Recording	CIF: PAL 1f/s-25f/s NTSC 1f/s-30f/s						
Video Display Split	Full and multiple screen display, 1 / 4 / 8 / 9 / 16						
Tour Display	Support						
Image Quality	1~6 level (level 6 is the best)						
Privacy Masking	Self-defined four-sided zone for Privacy masking for each camera						
Camera Lock	Camera locked for users						
Camera Adjustment	Adjust color according to different time period						
Video Information	Camera title, time, video loss, Camera lock, motion detection, recording						
TV Output Adjustment	Adjust TV output color & display zone						

Audio		
β—∅ÁiÖW	0²†²+-.°1∅)ñe∅-↵	â59<
βí-î £†Ê∂ú pMí£wøz00²†²+-.°1∅)ñe∅-↵		â59<
β—∅Álè('i	0²†²+-.°1∅)ñe∅-↵	â°03Ä
β—∅Ál%foñpò9‰	0∅l4\$	

Video Detection & Alarm	
Motion Detection	Zones: 192 (16*12) detection zones Sensitivity: 1~6 (level 6 is highest) Trigger recording, PTZ movement, tour, alarm, e-mail & FTP
Video Loss	Trigger recording, PTZ movement, tour, Alarm, e-mail & FTP

Camera blank	Trigger recording, PTZ movement, Tour, alarm, e-mail & FTP
Alarm Input	4/8/16 channel, programmable, ground, manual open/closed Trigger recording, PTZ movement, tour, Alarm, e-mail & FTP
Relay output	6 channel, 30VDC, 1A, NO/NC, form-C,

Hard Disk	
Hard Disk	4 SATA ports, 4 HDDs supported
Space Occupation	Audio, 14.4MB/H Video, 56~400MB/H
HDD Management	Hard disk hibernation technology, HDD faulty alarm & Raid (Redundancy)

Record Playback & Backup	
Recording Mode	Manual, continuous, video detection (including motion detection, camera blank, video loss), Alarm
Recording Priority	Manual >Alarm>Video Detection >Continuous
Recording Interval	1 to 120 minutes (default:60 minutes)
Overwrite Mode	Support
Raid Function	Support
Search Mode	Time/Date, Alarm, Motion Detection & exact search (accurate to second)
Playback	1 channel playback, pause, stop, rewind, fast next file, previous file, next camera, previous camera, full screen, repeat, shuffle, backup selection.
Digital Zoom	Selected zone can zoom into full screen during playback
Backup Mode	Flash stick/USBHDD/USBCD-RW/DVD RW/ network download

Network	
Interface	RJ-45 Port (10/100M)
Network Functions	TCP/IP, DHCP, DDNS, PPPOE, E-mail, FTP
Remote operation	Monitor, PTZ control, playback, system setting, file download, log information

Auxiliary Interface	
USB Interface	2 ports, 1 for mouse control, 1 for backup
RS232	DAHUA keyboard, PC communication
RS485	PTZ control

Environmental	
Power Supply	220V 50Hz / 110V 60Hz
Power consumption	25W/30W/40W
Working Temperature	-10C° ~+55C°
Working Humidity	10%~90%
Atmosphere Pressure	86kpa~106kpa
Dimension	1.5U, 440mmx460mmx68mm (W*D*H)
Weight	6.0KG

Note: Comparisons

Model	Audio Input	Loop Output	Matrix Output	Bidirectional talk	Audio Input
DH-DVR1604LN-S	No	No	No	No	No
DH-DVR1604LNH-S	4 channel	16 channel	1 channel		1 channel

Application

Recommended installation areas are Securities Companies, Change Booths, Casinos, Pawnshops, Jewelers, Galleries, Exhibition Halls, Department Stores, Convenience Stores, Discount Offices, Hospitals, Police Stations, Subway Stations, Airports, Banks etc.